


EC-UU004-5E-PVC-GY

Cable U/UTP 4 pair 0.47mm, Cat.5e, indoor, PVC, solid, grey,
305m



EC-UU004-5E-PVC-GY

Cable U/UTP 4 pair 0.47mm, Cat.5e, indoor, PVC, solid, grey,
305m

Detailed characteristics

Characteristic	Value
Category	5e
Bandwidth, MHz	100
Construction	U/UTP
Number of twisted pairs	4
Conductors material	Bare copper
Conductors type	Solid
Diameter of wire	0,47±0,005
Conductors insulation material	HDPE
Conductors insulation thickness, mm	0,19±0,02
Conductors insulation outer diameter, mm	0,85±0,05
Outer jacket material, mm	PVC
Usage	Indoor
Jacket thickness, mm	0,5±0,05
Jacket outer diameter, mm	5±0,2
Jacket color	Grey
Protective film	-
Rip cord	+
Mass density per unit length, kg/km	26,2
Bending radius without load, D	≥8
Bending radius with load, D	≥4
Tensile strength, H	≤80
Burst strength, H	≤400
Impedance, Ohm	100±15
Max. conductor resistance (DC), Ω/km	115
Standard compliance	Meets the standard requirements: Standard compliance ISO/IEC 11801, EN 50173 and TIA/EIA-568
Application supporters	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive
Temperature ranges °C	Storage from -20 to +60. Installation from 0 to +50. Exploitation from -20 to +60
Length, m	305
Package	Individual - cardboard box / transport cardboard box (2 individual boxes)
Package sizes (individual/transport), mm	200x350x350 / 420x370x370
Warranty	1 year